

HD30057

6 – 18 GHz Low Noise Amplifier

Features

- Frequency Range: 6-18GHz
- Gain: 27dB
- P_{1dB} : +10dBm
- IP3: +25dBm
- Noise Figure: 1.9dB (typ.)
- DC Power: 5V @ 65mA
- SMA-female connectorized

range of 6GHz to 18GHz.

Description

HD30057 is a high performance Microwave Low Noise (& Driver) Amplifier, with standard frequency









Electrical Specifications @+25 °C, $Z_{in}=Z_{out}=50\ \Omega$, $V_{supply} = +5VDC$

Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	GHz	6		18
Gain (S21) f = 6GHz	dB		26.0	
f = 12GHz	dB		27.0	
f = 18GHz	dB		22.5	
Gain Variation Over Temperature	dB/°C		0.02	0.03
Output Power P_{1dB}	dBm	+10	+11	
Saturated Output Power P_{Sat}	dBm		+13	
Output Third Order Intercept IP3	dBm		+25	
Noise Figure @12GHz	dB		1.9	2.2
Reverse Isolation (S12) @12GHz	dB		-43	
VSWR-Input (S11)	ratio:1	1.5 @6GHz	2.0 @12GHz	4.0 @18GHz
VSWR-Output (S22)	(unitless)	1.5 @6GHz	1.6 @12GHz	1.5 @18GHz
DC Power Supply - voltage	V	4.5	5.0	5.5
DC Power Supply - current	mA		65	75
Operating Temperature	°C	-40		+85
Size (RF/DC feedthru's excluded)	Inch	1.00 (L) x 0.75 (W) x 0.45 (H)		
Weight	Oz	0.6 (17 grams)		

HD30057

6 – 18 GHz Low Noise Amplifier







Typical Performance @+25 °C



HD30057

6 – 18 GHz Low Noise Amplifier

Typical Performance @+25 °C



HD Communications Corp.

2180 Fifth Avenue, Unit 4, Ronkonkoma, NY 11779

Tel: (631) 588-3877 Fax: (631) 588-3879 Email: sales@rfamplifiers.com


HD30057

6 – 18 GHz Low Noise Amplifier

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+20dBm
Supply Voltage (Survival)	+16V
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline



HD Communications Corp.

2180 Fifth Avenue, Unit 4, Ronkonkoma, NY 11779

06/13

Tel: (631) 588-3877 Fax: (631) 588-3879 Email: sales@rfamplifiers.com