

GSM Multi Carrier Power Amplifier

HD29605

925 – 960 MHz / 3.5Watts

Product Features

- Multi carrier power amplifier
- Solid State power amplifier
- High linearity and high efficiency
- 50 ohms input / output impedance

Application

- GSM Repeater

1. Electrical Specification.



Parameter	Specification	Remark
Frequency Range	925MHz~960MHz	35MHz BW
Output Power	3.5W	
Gain	41dB±1dB	
Gain Flatness	±0.5dB	
Gain Variation Over Temp.	±1dB max	-20°~+60°
IMD	< -60dBc	CW 10 tone
Harmonic	-45dBc max	
Input VSWR	1.5:1 max.	
Output VSWR	1.5:1 max.	Isolator Applied
Normal Operating Voltage	+28V	
DC Current Consumption	1.7A max.	@3.5W
Output protection	Isolator	
Shut-down Temp Level	85±5°	65±5° Auto Enable

2. Environmental Specification

Parameter	Specification	Remark
Operating Temperature	-20°~+60°	
Storage Temperature	-40°~+85°	
Relative Humidity	0%~90%	Non-condensing

3. Mechanical Specification.

Physical Dimension : 130mm X 120mm X 25mm

4. Pin Assignment

332-C Dante Court

Holbrook, NY 11741

Phone: 631-588-3877

Fax: 631-648-0518

sales@hdcom.com

GSM Multi Carrier Power Amplifier

HD29605

925 – 960 MHz / 3.5Watts

I/O Interface (D-Sub 9Pin Male)	1.	+28V_IN	
	2.	GND	
	3.	En/Disable Control	High & Open(Disable) Low (Enable)
	4.	VSWR Alarm	VSWR 5:1 (Over 25dBm)
	5.	FWD Power Monitor	33dBm = 4±0.1V (100mV/dB)
	6.	+28V_IN	
	7.	GND	
	8.	GND	
	9.	Over Temp Alarm	85±5° Shutdown 65±5° Auto Enable
DC INPUT Connector (D-Sub 9Pin Male)	1,6		+27V
	2,7,8		GND

Over Power Shutdown = 37±1dBm


GSM Multi Carrier Power Amplifier

HD29605

925 – 960 MHz / 3.5Watts

5. Electrical Test Data


5.1 IMD @Po=+35.5dBm(CW 2/10 Tone) / DC 28V, 1.4A



GSM Multi Carrier Power Amplifier

HD29605

925 – 960 MHz / 3.5Watts



332-C Dante Court

Holbrook, NY 11741

Phone: 631-588-3877

Fax: 631-648-0518

sales@hdcorn.com

GSM Multi Carrier Power Amplifier

HD29605

925 – 960 MHz / 3.5Watts

6. Outline Drawing

